



CorePro GLASS LED candles and lusters



CorePro LEDLusterND6.5-60W P45 E14840FRG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information	
Cap-Base	E14 [E14]
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LED
Flux measurement reference	Sphere
CE mark	Yes
EU RoHS compliant	Yes
Light Technical	
Color Code	840 [CCT of 4000K]
Luminous Flux	806 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	124.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Flickering value (PstLM)	1	
Stroboscopic effect value (SVM)	0.9	
Photobiological safety according to EN 62471 RG1		
Operating and Electrical		
Line Frequency	50 to 60 Hz	
Input Frequency	50 to 60 Hz	
Power Consumption	6.5 W	
Lamp Current (Nom)	50 mA	
Wattage Equivalent	60 W	
Starting Time (Nom)	0.5 s	
Warm-up time to 60% light	0.5 s	
Power Factor (Fraction)	0.55	
Voltage (Nom)	220-240 V	
Temperature		
T-Case Maximum (Nom)	55 ℃	


Datasheet, 2023, October 9 data subject to change

CorePro GLASS LED candles and lusters

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	P45 [P 45mm]
Approval and Application	
Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	387449
EyeComfort	Yes
Product Data	
Order product name	CorePro LEDLusterND6.5-60W P45
	E14840FRG


Full product name	CorePro LEDLusterND6.5-60W P45
	E14840FRG
Full product code	871951434762500
Order code	929002028892
Material Nr. (12NC)	929002028892
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514347625
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514347632

Dimensional drawing



Product	D	С
CorePro LEDLusterND6.5-60W P45 E14840FRG	45 mm	80 mm

Photometric data






Spectral Power Distribution Colour - CorePro LEDLusterND6.5-60W P45 E14840FRG

General uniform lighting - CorePro LEDLusterND6.5-60W P45 E14840FRG


CorePro GLASS LED candles and lusters


Photometric data



Light Distribution Diagram - CorePro LEDLusterND6.5-60W P45 E14840FRG

Lifetime





Lumen Maintenance Diagram - CorePro LEDLusterND6.5-60W P45 E14840FRG

Life Expectancy Diagram - CorePro LEDLusterND6.5-60W P45 E14840FRG



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.