








Conductor connection terminal 16-120mm², f. 5mm

Part no. AKU120/5
Catalog No. 107190

Delivery program

Product range			60 mm system Compact system
Basic function			Connections
Subrange			Universal conductor connection terminals
Description			With integrated retaining spring, open terminal chamber and captive terminal screw
Terminal area W x H		mm	17 x 15
Width		mm	23.5
Rated operational current	I _e	A	440
conductor			16 - 120 mm ² AWG 4 - MCM 250. directly terminated:    4 x 16 x 0.8 mm or 6 x 16 x 0.8 mm or 10 x 16 x 0.8 mm
For use with			All 5 mm thick flat busbars
Notes			
<input type="radio"/> round conductor, solid <input checked="" type="radio"/> Flexible, round conductor with correctly crimped ferrule <input type="radio"/> Round conductor, stranded <input type="radio"/> Section conductor, solid <input type="radio"/> Sector conductor, stranded  CU band  CU busbar			

Approvals

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

Dimensions

