

# ENSTO

Zacisk z różkiem do uziemiaczy

SEW20.3S

Typ	SEW20.3S
GTIN	6438100324834
Nazwa	Zacisk z różkiem do uziemiaczy PAS/BLL-T 50-157 mm <sup>2</sup> AlMgSi, with temporary earthing horn
Opis	SEW20.3S is used as a temporary earthing connector. The connector SEW20.3S includes an arc protection horn suitable for use with temporary earthing devices with screw fixing. The connector is watertight by silicone greased teeth. The connector is equipped with shear head nuts.

Producent



## Specyfikacje techniczne

### Certyfikaty

Normy: EN 50397-2

### Cechy

Do żył o przekroju: CC 50-157 mm

Pokrywa tworzywa sztucznego: SP16

### Parametry mechaniczne

Moment dokręcenia: 40 Nm

### Inne

Klasyfikacja ETIM: EC001062

### Wymiary

Masa Netto: 0,56 kg

## ETIM 7 Specyfikacje techniczne

etim

Nominal cross section main conductor SE:	50 ... 157 mm <sup>2</sup>
Nominal cross section main conductor SM:	50 ... 157 mm <sup>2</sup>
Material main conductor:	Aluminium
Material branch conductor:	Aluminium
Terminal insulated:	True
Clamping channel opening main conductor:	Closed
Clamping channel opening branch conductor:	Closed
Type of connection:	Insulation piercing connector IPC

## Opakowanie

---

### Paleta

Jednostka:	pcs
Rozmiar opakowania:	240
Głębokość:	1200 mm
Szerokość:	800 mm
Wysokość:	1350 mm

### Opakowanie

Jednostka:	pcs
Rozmiar opakowania:	24
Głębokość:	499 mm
Szerokość:	344 mm
Wysokość:	363 mm
Waga:	14,247 kg
Objętość :	62,311128 l