



TRYTYTKI SCV - czarne

materiał: poliamid 6.6

temp. montażu: -10°C do +60°C

temp. pracy: -40°C do +85°C

wytrzymałość dielektryczna: 50kV/mm²

absorpcja wody: 2,5% (50% R.H., +23°C)

palność: UL-94 V2

tolerancja: ±5%

TYP	ROZMIAR [mm]	max/min ŚREDNICA [mm]	WYTRZYMAŁOŚĆ [kg]	OPAKOWANIE [szt]	
SCV-100MW	100x2,5	24/2	11	100	■
SCV-140MW	135x2,5	35/2	11	100	■
SCV-165MW	160x2,5	42/2	11	100	■
SCV-200MW	200x2,5	55/2	11	100	■
SCV-140IW	140x3,5	36/3	20	100	■
SCV-200IW	200x3,5	55/3	20	100	■
SCV-250IW	250x3,5	70/3	20	100	■
SCV-300IW	280x3,5	80/3	20	100	■
SCV-370IW	360x3,5	103/3	20	100	■
SCV-190STW	200x4,5	51/3	28	100	■
SCV-250STW	250x4,5	68/5	28	100	■
SCV-280STW	280x4,5	76/5	28	100	■
SCV-370STW	360x4,5	101/5	28	100	■
SCV-430STW	430x4,5	123/5	28	100	■
SCV-200HW	200x7,5	48/5	65	100	■
SCV-300HW	280x7,5	76/5	65	100	■
SCV-370HW	360x7,5	101/5	65	100	■
SCV-430HW	450x7,5	130/20	65	100	■
SCV-530HW	540x7,5	160/20	65	100	■
SCV-750HW	750x7,5	222/32	65	100	■
SCV-770HWL	780x9,0	235/22	80	100	■
SCV-1170HWL	1220x9,0	375/40	80	100	■
SCV-500EHW	500x12,5	140/10	120	50	■
SCV-750EHW	750x12,5	222/40	120	50	■



złącz

TRYTYT.COM!