## Product data sheet Characteristics

# DF101PV

Fuse carrier photovoltaic TeSys DF, 1P 32A, fuse size 10x38 mm



Main		
Range	TeSys	
Product name	TeSys DF	
Product or component type	Fuse carrier	
Device short name	DF10	
Poles description	1P	
Fuse size	10 x 38 mm	
Control type	Toggle padlockable	
Utilisation category	AC-20B conforming to IEC 60947-3 DC-20B conforming to IEC 60947-3	
[Ue] rated operational voltage	1000 V DC	
[le] rated operational current	32 A	
[Ui] rated insulation voltage	1000 V DC	
[Uimp] rated impulse withstand voltage	6 kV	
Overvoltage category	III	
Short-circuit withstand	120 kA 400 V conforming to IEC 60947-3	
Power dissipation in W	3 W maximum power dissipation by fuse	
Complementary		
Standards	CSA C22.2 No 4248-19 UL 4248-19	

## Complementary

Ctandarda	CCA C22.2 No. 4249.40	
Standards	CSA C22.2 No 4248-19	:
	UL 4248-19	
	EN/IEC 60269-2	•
	CSA C22.2 No 4248-1	,
	UL 4248-1	• •
Product certifications	UL recognized	
	IEC	
	EAC	-
	CCC	
	CSA	:
Mounting support	35 mm symmetrical DIN rail	
Mounting position	Vertical (tolerance: +/- 23°)	
Connections - terminals	Screw clamp terminals 1 cable(s) 116 mm²rigid	
	Screw clamp terminals 2 cable(s) 16 mm²riqid	-
	Screw clamp terminals 1 cable(s) 116 mm²flexible with or without	
	Screw clamp terminals 2 cable(s) 16 mm²flexible with or without	
Tightening torque	2 N.m - with screwdriver PZ2	

#### 2 N.m - with screwdriver flat Ø 5.5 mm

Height	79.5 mm
Width	17.5 mm
Depth	61 mm
Net weight	0.042 kg
Quantity per set	Set of 12

#### Environment

Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-4070 °C with derating above 20°C
Operating altitude	02000 m without derating
IP degree of protection	IP20
Pollution degree	3
Fire resistance	960 °C conforming to IEC 60695-2-1
Compatibility code	DF10

## Packing Units

Package 1 Weight	0.063 kg	
Package 1 Height	0.885 dm	
Package 1 width	0.175 dm	
Package 1 Length	0.645 dm	

## Offer Sustainability

REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

## Contractual warranty

Warranty	18 months
----------	-----------