

Product Specification Sheet



Technical Information

| Watts: | 20 | | Dimmable: | No |
|----------------|--------------------|---|------------------------|------------------|
| Lumens: | 1600 | | Warranty (Years): | 5 |
| Beam Angle: | 100 | | PF: | >0.9 |
| Unit Color: | White | | CRI: | >80 |
| Body Type: | Die Cast Aluminium | n | Operation Temperature: | -20 to +45°c |
| Long life: | 30,000 Hours | | Input Power: | AC:220-240V,50Hz |
| LED Chip Type: | SMD | | Sensor Compatibility: | Yes |
| IP Rating: | IP65 | | | |

Features

- Perfect replacement of Metal Hallide Floodlight, High Pressure Sodium Floodlight & Halogen Floodlight
- Fascia glass sealed with SILICONE RUBBER ensuring superior waterproof /airtight performance
- High Power LED Samsung Chip
- Constant current Integrated IC driver
- Premium Quality Die Casting Aluminium Body
- Corrosion Resistant
 - Available in different color options of White , Day White & Warm White
 - Complies with LM-80
 - Excellent coverage for area and facade lighting
 - Application Building Facade, Sports Facilities, Industrial, Commercial Bill Boards & Hoardings, Parking Lots etc



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

Packaging

| Unit Details | | Listing Details | |
|---------------------------------|----------|-----------------|---------------|
| Gross Weight(GW) Kgs | 0.45 | EAN Code | 3800157630993 |
| Unit CBM | 0.000896 | Commodity Code | 9405403990 |
| Master Box Packaging | | | |
| Master Box Qty (Pcs Per Carton) | 20 | | |
| Qty Per Pallet | 960 | | |
| | | | |

